

DH Sandbox API Documentation for Public Supplier V2

Content

1	Documentation version history	2
2	Preface	3
3	Environments.....	4
4	Use case scenarios	5
4.1	Access rights.....	5
4.1.1	Assign Right and View Assignment Details.....	5
4.1.2	Cancel Assigned Right	9
4.2	Orders	11
4.2.1	Order and View Automated Amount on Object Level Report – Consumption / Net Metering Objects	11
4.2.2	Order and View Automated Amount on Object Level Report – Net Billing Objects	12
4.2.3	Order and View Balance Data Report	16
4.2.4	Order and View Generation by Type Report	17
4.2.5	Order and View Balance Data by Contract Type Report.....	18
4.2.6	Order and View Cumulative Quantities Report Based on Granted Rights	19
4.2.7	View Report List.....	20
4.2.8	View Report Line Count.....	22

1 Documentation version history

The table below provides information on document version history:

Version	Date	Description
2.0.0	2026-08-21	This version introduces a new approach to documentation. All prior versions remain available in the earlier documentation set.

Note: Changes in the table marked in white are already deployed, while those marked in green will be deployed soon.

2 Preface

This document is designed to guide through the process of effectively utilizing the sandbox environment. The sandbox environment is intended for testing and validating integration with the DH Platform without impacting live operations. It offers a safe space to explore API functionalities and execute test scenarios using mock data, as described in the [Use Case Scenarios](#) section.



Before using the Sandbox, we recommend reviewing the API structure and endpoint descriptions in the latest version of the DH API documentation for public supplier (DH_API_documentation_for_public_supplier_latestVersion.pdf).

3 Environments

The DH platform provides two accessible environments:

- **Production environment** for live operations
- **Sandbox environment** with mock data for testing purposes

For full environment details, including base URLs and authorization, please refer to the latest version of the DH API documentation for public supplier ([DH_API_documentation_for_public_supplier_latestVersion.pdf](#)).

4 Use case scenarios

This section presents technical use case scenarios to demonstrate API interaction within the sandbox environment using mock data. Each scenario supports end-to-end testing of workflows, API calls, and response handling.

To improve clarity and navigation, cases are grouped by functional domains (for example: **Access Rights, Orders**). This structure helps quickly locate relevant scenarios based on the system functionality.

Each use case is structured into the following components:

- **Overview:** Defines the logical sequence of actions in the use case.
- **Workflow Steps:** Lists the API endpoints and their execution order.
- **Example Flow:** Shows detailed mock request and response examples illustrating expected behavior.

4.1 Access rights

4.1.1 Assign Right and View Assignment Details

This scenario describes how to:

- Identify the object that requires an access rights assignment.
- Assign a right to an object.
- View the details of the assigned right in the right list.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Identify Object for Right Assignment	POST /gateway/public-supplier/object/all/active/list
2	Assign Right to Object	POST /gateway/public-supplier/access-right
3	View Assigned Right Details	POST /gateway/public-supplier/access-rights/search

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Identify Object for Right Assignment

Request

```
{
  "objectDataConsentSign": true,
  "objectNumber": "20240314"
}
```

Response

```
[
  {
    "personName": "Vardenis",
    "personSurname": "Pavardenis024",
```

```
"personCode": "*****314",
"consumerCode": "20240314",
"objectNumber": "20240314",
"metersAmount": 1,
"autoMetersAmount": 1,
"smartMeterInstallationDate": "2022-12-14",
"meters": [
  {
    "meterNumber": "SAG1010101411111",
    "meterAutomated": true,
    "automationSystem": "MDM",
    "meterScaleLength": 6,
    "scales": [
      {
        "scaleIdentifier": "+WsumT2",
        "scaleProduct": "NK"
      },
      {
        "scaleIdentifier": "+WsumT1",
        "scaleProduct": "DD"
      }
    ]
  }
],
"objectAddress": "Kauno g. 1, Kėdainiai",
"contractType": "SBTS",
"contractModel": "BSS",
"supplierType": "NT",
"timeLimitedObjectValidTo": null,
"tariffPlan": "Standartinis",
"tariffPlanChangeDate": "2022-12-14",
"timeZone": "2",
"ownershipDocumentNumber": null,
"supplyOwnership": "NOT_MY",
"contractStart": null,
"contractEnd": null,
"accountingType": "NET_METERING",
"objectPowers": [
  {
    "powerType": "LOG",
    "power": 8,
    "powerValidFrom": "2023-07-01",
    "powerValidTo": null
  },
  {
    "powerType": "LGG",
    "power": 5,
    "powerValidFrom": "2023-07-01",
    "powerValidTo": null
  },
]
```

```
{
  "powerType": "IOG",
  "power": 8,
  "powerValidFrom": "2023-07-01",
  "powerValidTo": null
},
{
  "powerType": "IGG",
  "power": 5.4,
  "powerValidFrom": "2023-07-01",
  "powerValidTo": null
}
],
"generatingObjectGroup": {
  "generatingGroup": 1,
  "generatingObjectPriorityGroup": 2
},
"objectFutureSuppliers": [],
"usedPowerPlants": [
  {
    "powerPlantObjectNumber": "20240314",
    "powerPlantType": "S",
    "generatingObjectType": "G",
    "generatingPower": 1,
    "powerPlantValidFrom": "2022-12-14",
    "powerPlantValidTo": null,
    "accountingScheme": "NET_METERING",
    "accountingSchemeValidFrom": "2022-12-14",
    "accountingSchemeValidTo": null,
    "accountingSchemeChangeDate": "2024-01-01",
    "payoffMethod": "P",
    "payoffMethodChangeDate": "2024-01-01"
  }
],
"objectLatestSupplyState": {
  "state": "T",
  "stateValidFrom": "1996-12-11",
  "stateValidTo": null
},
"contact": {
  "mobPhoneNoNetwork": null,
  "mobPhoneNo2Network": null,
  "mobPhoneInvoice": null,
  "phoneNoNetwork": null,
  "emailNetwork": null,
  "emailNetwork2": null,
  "emailInvoice": null
},
"consumptionAverage": 70.6,
"consumptionAverageCalculationDate": "2024-02-08",
```

```
"consumptionAverageCalculationMonthsCount": 10,
"powerPlantObjectType": "S"
}
]
```

Step: Assign Right to Object

Request

```
{
  "accessRightInformation": [
    {
      "accessRightEmailAddress": "vardenis.pavardenis024@a.lt",
      "accessRightNote": null,
      "accessRightPhoneNo": "+37063333333",
      "accessRightValidTo": "YYYY-MM-DD", // Any future date within 1 year
      "objectNumber": "20240314"
    }
  ],
  "consentSign": true,
  "personBrithDate": null,
  "personCode": "99201201314",
  "personName": "Vardenis",
  "personSurname": "Pavardenis024"
}
```

Response

```
[
  {
    "accessRightId": "<unique-access-right-id>"
  }
]
```

Step: View Assigned Right Details

Request

```
{
  "accessRightId": 100040,
  "consumerCode": "20240314",
  "objectNumber": "20240314",
  "generatingObjectType": "G",
  "contractType": "SBTS",
  "contractModel": "BSS",
  "accountingType": "NET_METERING",
  "powerPlantType": "S"
}
```

Response

```
[
  {
    "accessRightId": 100040,
    "accessRightValidFrom": "2026-01-06T15:17:07",
  }
]
```



```

"accessRightValidTo": "2126-01-06T15:17:07",
"daysLeft": "<days-remaining-until-access-expires>",
"accessRightSource": "DATAHUB",
"userName": "PUBLIC",
"objectNumber": "20240314",
"objectAddress": "Kauno g. 1, Kėdainiai",
"powerPlantObjectType": "S",
"contractModel": "BSS",
"supplierType": "NT",
"tariffPlan": "Standartinis",
"timeZone": "2",
"accountingType": "NET_METERING",
"usedPowerPlants": [
  {
    "powerPlantObjectNumber": "20240314",
    "powerPlantType": "S",
    "generatingObjectType": "G",
    "accountingScheme": "NET_METERING",
    "payoffMethod": "P",
    "generatingPower": 1
  }
],
"automationLevel": "FULL",
"contractType": "SBTS",
"personName": "Vardenis",
"personSurname": "Pavardenis024",
"personCode": "*****314",
"consumerCode": "20240314",
"accessRightPhoneNo": "+37063333333",
"accessRightEmailAddress": "vardenis.pavardenis024@a.lt",
"accessRightNote": null
}
]

```

4.1.2 Cancel Assigned Right

This scenario describes how to:

- Identify the access right that needs to be canceled.
- Cancel the assigned access right.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Identify Right to Cancel	POST /gateway/public-supplier/access-rights/search
2	Cancel Assigned Access Right	POST /gateway/public-supplier/access-right/{accessRightId}/cancel

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Identify Right to Cancel

Request

```
{
  "accessRightId": 100041,
  "objectNumber": "20240226"
}
```

Response

```
[
  {
    "accessRightId": 100041,
    "accessRightValidFrom": "2026-01-06T15:17:07",
    "accessRightValidTo": "2126-01-06T15:17:07",
    "daysLeft": <days-remaining-until-access-expires>,
    "accessRightSource": "DATAHUB",
    "userName": "PUBLIC",
    "objectNumber": "20240226",
    "objectAddress": "Saulės g. 26, Klaipėda",
    "powerPlantObjectType": null,
    "contractModel": "BSS",
    "supplierType": "GT",
    "tariffPlan": "Namai",
    "timeZone": "2",
    "accountingType": "NET_BILLING",
    "usedPowerPlants": [
      {
        "powerPlantObjectNumber": "20240227",
        "powerPlantType": "S",
        "generatingObjectType": "N",
        "accountingScheme": "NET_BILLING",
        "payoffMethod": null,
        "generatingPower": 9
      },
      {
        "powerPlantObjectNumber": "20240228",
        "powerPlantType": "S",
        "generatingObjectType": "N",
        "accountingScheme": "NET_BILLING",
        "payoffMethod": null,
        "generatingPower": 5
      }
    ],
    "automationLevel": "FULL",
    "contractType": "SBTS",
    "personName": "Vardenis",
  }
]
```

```

    "personSurname": "Pavardenis26",
    "personCode": "*****444",
    "consumerCode": "20240226",
    "accessRightPhoneNo": null,
    "accessRightEmailAddress": "Vardenis.Pavardenis26@test.lt",
    "accessRightNote": null
  }
]

```

Step: Cancel Assigned Access Right

Request

```
POST /gateway/public-supplier/access-right/100041/cancel
```

Response

If the request is successful, an HTTP 200 Created message is returned.

4.2 Orders

4.2.1 Order and View Automated Amount on Object Level Report – Consumption / Net Metering Objects

Preconditions:

- A non-generating object or an object using a Net metering accounting scheme must be available before executing this scenario.
- Data from the ordered report can only be viewed once the order status is marked as *Completed*. To verify the order status, refer to the [View Report List](#) scenario and apply the relevant filters (such as *latestStatus*, *orderTypes*, *orderId*).

This scenario describes how to:

- Order the **Automated amount on object level** report.
- Retrieve data from the ordered **Automated amount on object level** report.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Order Report	POST /gateway/public-supplier/order/data-hr-15min-obj-lvl
2	Retrieve Report Data	GET /gateway/public-supplier/order/{orderId}/data-hr-15min-obj-lvl

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Order Report

Note: Multiple POST request variants are possible (different combinations of parameters, e.g., consumption category). The GET response below shows one example with multiple consumption categories.

Example 1 - Report with consumption data

Request

```
{
  "dateFrom": "YYYY-MM-DD", // Any date within 36 months
  "dateTo": "YYYY-MM-DD", // Value must not exceed 12 months from dateFrom
  "consumptionCategories": [
    "P+"
  ],
  "objectNumbers": [
    "20240106"
  ],
  "interval": "HOUR"
}
```

Example 2 - Report with consumption and generation data

Request

```
{
  "dateFrom": "YYYY-MM-DD", // Any date within 36 months
  "dateTo": "YYYY-MM-DD", // Value must not exceed 12 months from dateFrom
  "consumptionCategories": [
    "P+",
    "P-"
  ],
  "objectNumbers": [
    "20240106"
  ],
  "interval": "HOUR"
}
```

All requests return the same response

```
{
  "orderId": "<unique-order-id>"
}
```

Step: Retrieve Report Data

Request

GET /gateway/public-supplier/order/100054/data-hr-15min-obj-lvl

Response

Response is provided in the Automated_amount_on_object_level_report_100054.json file.

4.2.2 Order and View Automated Amount on Object Level Report – Net Billing Objects

Preconditions:

- An object with a **Net billing** accounting scheme must be available before executing this scenario.
- Data from the ordered report can only be viewed once the order status is marked as *Completed*. To verify the order status, refer to the [View Report List](#) scenario and apply the relevant filters (such as *latestStatus*, *orderTypes*, *orderId*).

This scenario describes how to:

- Order the **Automated amount on object level** report without recalculating data.
- Retrieve data from the ordered **Automated amount on object level** report.
- Order the **Net billing interval data change** report to check for changes that may require recalculating the **Automated amount on object level** report.
- Retrieve data from the ordered **Net billing interval data change** report.
- Order the **Automated amount on object level** report with data recalculation.
- Retrieve data from the ordered **Automated amount on object level** report.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Order Automated Amount on Object Level Report without Data Recalculation	POST /gateway/public-supplier/order/data-hr-15min-obj-lvl
2	Retrieve Automated Amount Report (Non – Recalculated Data)	GET /gateway/public-supplier/order/{orderId}/data-hr-15min-obj-lvl
3	Order Net billing Interval Data Change Report	POST /gateway/public-supplier/order/data-hr-15min-history-changes
4	Retrieve Net Billing Interval Data Change Report	GET /gateway/public-supplier/order/{orderId}/data-hr-15min-history-changes
5	Order Automated Amount on Object Level Report with Data Recalculation	POST /gateway/public-supplier/order/data-hr-15min-obj-lvl
6	Retrieve Automated Amount Report (Recalculated Data)	GET /gateway/public-supplier/order/{orderId}/data-hr-15min-obj-lvl

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Order Automated Amount on Object Level Report without Data Recalculation

Example 1 - Hourly data report (power plant data aggregated)

Request

```
{
  "consumptionCategories": [
    "P+",
    "P- "
  ],
```

```
"dateFrom": "YYYY-MM-DD", // Any date within 36 months
"dateTo": "YYYY-MM-DD", // Value must not exceed 12 months from dateFrom
"interval": "HOUR",
"objectNumbers": [
    "20240229"
],
"netBilling": {
    "intervalData": true,
    "intervalDataRecalculation": false,
    "intervalDataDetailed": false
}
```

Response

```
{
  "orderId": "<unique-order-id>"
}
```

Example 2 - Hourly data report (including detailed power plant data)

Request

```
{
  "consumptionCategories": [
    "P+",
    "P-"
  ],
  "dateFrom": "YYYY-MM-DD", // Any date within 36 months
  "dateTo": "YYYY-MM-DD", // Value must not exceed 12 months from dateFrom
  "interval": "HOUR",
  "objectNumbers": [
    "20240229"
  ],
  "netBilling": {
    "intervalData": true,
    "intervalDataRecalculation": false,
    "intervalDataDetailed": true
  }
}
```

Response

```
{
  "orderId": "<unique-order-id>"
}
```

Step: Retrieve Automated Amount Report (Non – Recalculated Data)

Example 1 - Hourly data report (power plant data aggregated)

Request

```
GET /gateway/public-supplier/order/100063/data-hr-15min-obj-lvl
```

Response

Response is provided in the Automated_amount_on_object_level_report_100063.json file.

Example 2 - Hourly data report (including detailed power plant data)

Request

```
GET /gateway/public-supplier/order/100064/data-hr-15min-obj-lvl
```

Response

Response is provided in the Automated_amount_on_object_level_report_100064.json file.

Step: Order Net billing Interval Data Change Report

Request

```
{
  "dateFrom": "YYYY-MM-DD", // Any date, not older than 3 previous accounting months
  "objectNumbers": [
    "20240229"
  ]
}
```

Response

```
{
  "orderId": "<unique-order-id>"
}
```

Step: Retrieve Net Billing Interval Data Change Report

Request

```
GET /gateway/public-supplier/order/100065/data-hr-15min-history-changes
```

Response

Response is provided in the Net_billing_interval_data_change_report_100065.json file.

Step: Order Automated Amount on Object Level Report with Data Recalculation

Request

```
{
  "consumptionCategories": [
    "P+",
    "P-"
  ],
  "dateFrom": "YYYY-MM-DD", // Recalculation billing period date within the last 36 months
  "dateTo": "YYYY-MM-DD", // Value must not exceed 1 accounting period from dateFrom
  "interval": "HOUR",
  "objectNumbers": [
    "20240229"
  ],
}
```

```
"netBilling": {
  "intervalData": true,
  "intervalDataRecalculation": true,
  "intervalDataDetailed": true
}
```

Response

```
{
  "orderId": "<unique-order-id>"
}
```

Step 6: Retrieve Automated Amount Report (Recalculated Data)

Request

```
GET /gateway/public-supplier/order/100066/data-hr-15min-obj-lvl
```

Response

Response is provided in the Automated_amount_on_object_level_report_100066.json file.

4.2.3 Order and View Balance Data Report

Preconditions:

- Data from the ordered report can only be viewed once the order status is marked as *Completed*. To verify the order status, refer to the [View Report List](#) scenario and apply the relevant filters (such as *latestStatus*, *orderTypes*, *orderId*).

This scenario describes how to:

- Order the **Balance data** report.
- Retrieve data from the ordered **Balance data** report.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Order Report	POST /gateway/public-supplier/order/balance-data
2	Retrieve Report Data	GET /gateway/public-supplier/order/{orderId}/balance-data

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Order Report

Request

```
{
  "dateFrom": "YYYY-MM-DD", // Any date within 36 months
  "dateTo": "YYYY-MM-DD", // Value must not exceed 1 accounting period from dateFrom
  "interval": "HOUR"
}
```


Response

```
{
  "orderId": "<unique-order-id>"
}
```

Step: Retrieve Report Data

Request

GET /gateway/public-supplier/order/100075/balance-data

Response

Response is provided in the Balance_data_report_100075.json file.

4.2.4 Order and View Generation by Type Report

Preconditions:

- Data from the ordered report can only be viewed once the order status is marked as *Completed*. To verify the order status, refer to the [View Report List](#) scenario and apply the relevant filters (such as *latestStatus*, *orderTypes*, *orderId*).

This scenario describes how to:

- Order the **Generation by type** report.
- Retrieve data from the ordered **Generation by type** report.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Order Report	POST /gateway/public-supplier/order/balance-by-generation-type
2	Retrieve Report Data	GET /gateway/public-supplier/order/{orderId}/balance-by-generation-type

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Order Report

Request

```
{
  "generationType": "S",
  "dateFrom": "YYYY-DD-MM", // Any date within 36 months
  "dateTo": "YYYY-MM-DD", // Value must not exceed 1 accounting period from dateFrom
  "interval": "HOUR"
}
```

Response

```
{
  "orderId": "<unique-order-id>"
}
```

Step: Retrieve Report Data

Request
GET /gateway/public-supplier/order/100076/balance-by-generation-type

Response
Response is provided in the Balance_by_generation_type_100076.json file.

4.2.5 Order and View Balance Data by Contract Type Report

Preconditions:

- Data from the ordered report can only be viewed once the order status is marked as *Completed*. To verify the order status, refer to the [View Report List](#) scenario and apply the relevant filters (such as *latestStatus*, *orderTypes*, *orderId*).

This scenario describes how to:

- Order the **Balance data by contract type** report.
- Retrieve data from the ordered **Balance data by contract type** report.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Order Report	POST /gateway/public-supplier/order/balance-data-by-contract-type
2	Retrieve Report Data	GET /gateway/public-supplier/order/{orderId}/balance-data-by-contract-type

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Order Report

Request

```
{
  "contractType": "SBTS",
  "dateFrom": "YYYY-MM-DD", // Any date within 36 months
  "dateTo": "YYYY-MM-DD", // Value must not exceed 1 accounting period from dateFrom
  "interval": "HOUR"
}
```

Response

```
{
  "orderId": "<unique-order-id>"
}
```

Step: Retrieve Report Data

Request

GET /gateway/public-supplier/order/100105/balance-data-by-contract-type

Response

Response is provided in the Balance_data_by_contract_type_report_100105.json file.

4.2.6 Order and View Cumulative Quantities Report Based on Granted Rights

Preconditions:

- The scenario requires the object to have an assigned right. If the right has not been assigned yet, follow the process outlined in the [Assign Right and View Assignment Details](#) scenario.
- Data from the ordered report can only be viewed once the order status is marked as *Completed*. To verify the order status, refer to the [View Report List](#) scenario and apply the relevant filters (such as *latestStatus*, *orderTypes*, *orderId*).

This scenario describes how to:

- Order the **Cumulative Quantities** report.
- Retrieve data from the ordered **Cumulative Quantities** report.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	Order Report	POST /gateway/public-supplier/order/data-sum-obj-lvl-acr
2	Retrieve Report Data	GET /gateway/public-supplier/order/{orderId}/data-sum-obj-lvl-acr

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: Order Report

Request

{
 "dateFrom": "YYYY-MM-DD", // First day of month, within 36 months
 "dateTo": "YYYY-MM-DD", // Last day of month (or today, if it is the current month)
 "objectNumbers": [
 "20240226"
]
}

Response

{
 "orderId": "<unique-order-id>"
}

Step: Retrieve Report Data

Request

GET /gateway/public-supplier/order/100110/data-sum-obj-lvl-acr

Response is provided in the
Cumulative_quantities_report_based_on_granted_rights_100110.json file.

Preconditions:

- This scenario describes how to:**

- The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	View Report List	POST /gateway/public-supplier/order/list

Step: View Report List (Filtered Examples)

Request

```
{
  "orderId": 100054
}
```

```
[
  {
    "orderId": 100054,
    "orderType": "data-hr-15min-obj-lvl",
    "submittedDate": "2024-01-04T10:33:50.769",
    "dateFrom": "2023-12-01",
    "dateTo": "2023-12-01",
    "orderParameters": "{\"consumptionCategories\": [\"P+\", \"P-\"], \"objectNumbers\": [\"20240226\"], \"interval\": \"HOUR\"}",
    "latestStatus": "IV",
    "statusDate": "2024-01-04T10:33:53.379",
    "expireDate": "2124-01-05T10:33:52.379",
    "auto": false,
    "userName": "PUBLIC"
  }
]
```

Example 2: Search by multiple parameters

Request

```
{
  "latestStatuses": [
    "IV"
  ],
  "orderId": 100075,
  "orderTypes": [
    "balance-data"
  ]
}
```

Response

```
[
  {
    "orderId": 100075,
    "orderType": "balance-data",
    "submittedDate": "2024-03-04T08:30:48.302",
    "dateFrom": "2024-03-01",
    "dateTo": "2024-03-01",
    "orderParameters": "{\"interval\":\"HOURL\"}",
    "latestStatus": "IV",
    "statusDate": "2024-03-04T08:30:48.624",
    "expireDate": "2124-03-05T08:30:48.624",
    "auto": false,
    "userName": "PUBLIC"
  }
]
```

Example 3 - Search by all parameters

Request

```
{
  "auto": false,
  "dateFrom": "2025-12-01",
  "dateTo": "2025-12-31",
  "latestStatuses": [
    "IV"
  ],
  "orderId": 100110,
  "orderParametersSearch": "{\"objectNumbers\":[\"20240106\"]}",
  "orderTypes": [
    "data-sum-obj-lvl-acr"
  ],
  "submittedDateFrom": "2026-01-06T00:00:00.000",
  "submittedDateTo": "2026-01-07T00:00:00.000",
  "userNameSearch": "PUBLIC"
}
```

```
}
```

Response

```
[
  {
    "orderId": 100110,
    "orderType": "data-sum-obj-lvl-acr",
    "submittedDate": "2026-01-06T15:24:01.165",
    "dateFrom": "2025-12-01",
    "dateTo": "2025-12-31",
    "orderParameters": "{\"objectNumbers\": [\"20240106\"]}",
    "latestStatus": "IV",
    "statusDate": "2026-01-06T15:24:02.219",
    "expireDate": "2056-01-07T15:24:02.219",
    "auto": false,
    "userName": "PUBLIC"
  }
]
```

4.2.8 View Report Line Count

Preconditions:

- A report with *Completed* status must be created before executing this scenario.

This scenario describes how to:

- View the line count of the report with *Completed* status.

The following table maps each step to its corresponding API endpoint:

Step	Description	API Endpoint
1	View Report Line Count	GET /gateway/public-supplier/order/{orderId}/count

The following examples illustrate each step from the workflow table above, showing sample requests and responses for the corresponding API calls.

Step: View Report Line Count

Request

```
GET /gateway/public-supplier/order/100054/count
```

Response

```
{
  "count": 1
}
```